

Food &
hygiene



Dosatron is one of
the main actor in the
processes detergence
and **disinfection** in the
Food & Hygiene Industry

NEW APP



www.dosatron.com



©DOSATRON INTERNATIONAL S.A.S 2023 - DOCFAPHEN-02/23 - Photo credit : Adobe Stock

DOSATRON INTERNATIONAL S.A.S

Rue Pascal - BP 6 - 33370 TRESSES (Bordeaux) - FRANCE

Tel. 33 (0)5 57 97 11 11 - Fax. 33 (0)5 57 97 11 29 / 33 (0)5 57 97 10 85

info@dosatron.com - www.dosatron.com



CIP (clean in place) with simple installation:
D3 range can be used



	D3RE3000	D3RE2	D3RE5	D3RE10	D3RE25IE
Operating flow min./max.	10l/h mini - 3 m³/h maxi [1/3 US Pint/min (min.) - 14 US GPM (max.)]				10l/h mini - 2 m³/h maxi [1/3 US Pint/min (min.) - 9 US GPM (max.)]
Maximum operating temperature	40°C / 104°F				
Operating water pressure min./max.	0,3 - 6 bar [4.3 - 85 PSI]			0,5 - 6 bar [7 - 85 PSI]	0,5 - 4 bar [7 - 57 PSI]
Dosing % min./max.	0,03% to 0,3% 1:3000 - 1:333	0,2% to 2% 1:500 - 1:50	0,5% to 5% 1:200 - 1:20	1% to 10% 1:100 - 1:10	5% to 25% 1:20 - 1:4
Version serial option	    	      	      	      	     
Connection	¾" Male BSP/NPT - Ø20x27 mm				

Centralised cleaning system
with system connected to satellites:
D8 range can be used



	D8RE3000	D8RE2	D8RE5
Operating flow min./max.	500l/h mini - 8 m³/h maxi [2.2 US Pint/min (min.) - 40 US GPM (max.)]		
Maximum operating temperature	40°C / 104°F		
Operating water pressure min./max.	0,15 - 8 bar [2.2 - 116 PSI]		
Dosing % min./max.	0,03% to 0,125% 1:3000 - 1:800	0,2% to 2% 1:500 - 1:50	1% to 5% 1:100 - 1:20
Version serial option	    	    	    
Connection	1 ½" Male BSP/NPT - Ø40x49 mm		



Centralised cleaning system



Standard installation



Entry way sanitation

Entry way sanitation:
D25 range can be used



	D25RE2	D25RE5
Operating flow min./max.	10l/h mini - 2.5 m³/h maxi [1/3 US Pint/min (min.) - 11 US GPM (max.)]	
Maximum operating temperature	40°C / 104°F	
Operating water pressure min./max.	0.3 - 6 bar [4.3 - 85 PSI]	
Dosing % min./max.	0.2% to 2% 1:500 - 1:50	1% to 5% 1:100 - 1:20
Version serial option	      	     
Connection	¾" Male BSP/NPT - Ø20x27 mm	



Dosing system for entry way sanitation